

Product Data Sheet

DuoNPFL™ 330-24SD

Neoprene, Flock Lined, 24mil (0.61mm) Work Glove



Material	Neoprene
Length	330 mm
Weight	94 g
Thickness	24 mil / 0.61mm
Cuff Finish	Straight
Colour	Bi colour- Blue/Yellow
Interior Finish	Flock Lined
Grip	Diamond
Material	Neoprene

Features

- Double dipped coating provides extra protection
- Anatomical shape offers comfort and minimizes hand fatigue
- Embossed diamond pattern offers excellent grip
- Pure cotton flock lining absorbs sweat whilst keeping hand dry and cool

Applicable Industries

- Chemical
- Cleaning & Janitorial
- Construction
- Manufacturing
- General Handling
- Outdoor work
- Waste Management

Glove Type


- General Handling Gloves
- Chemical Resistant Glove

Hazard

- Chemical
- General household

Certifications

CE Cat iii certificate
 EN 420:2003+A1:2009
 EN 388:2016 (3121X)
 EN 374-1:2016 (AKLMNOP) (Type A)
 EN 374-2:2014
 EN 374-4:2013



Dimensions

Size	Length (mm)	Palm width (mm)	Thickness BOP (mm)	Weight Per Pair (g)
Small	330±10	95±3	0.60 ± 0.03	88 ± 3
Medium	330±10	107±3	0.60 ± 0.03	94 ± 3
Large	330±10	113±3	0.60 ± 0.03	100 ± 3
Extra Large	330±10	118±3	0.60 ± 0.03	106 ± 3

Tensile Properties

PROPERTY	BEFORE AGEING	AFTER AGEING
Tensile Strength (Mpa)	>16	>14
Elongation at break (%)	>600	>400

Utility Properties

Protein content µg/g	FLOCK LINED	UNLINED
	< 200	

Degree of Conformance

CHARACTERISTICS	SAMPLE SIZE	VALUE
Dimension	According to the lot size	Si – 2.5
Tension	According to the lot size	Sii – 4.0
Critical Defects – AQL %	According to the lot size	Gii – 0.65
Holes - AQL %	According to the lot size	Gii – 1.5
Major Defects – AQL %	According to the lot size	Gii – 2.5
Minor Defects – AQL %	According to the lot size	Gii – 4.0

Packaging

Description 12 Pairs with a Sleeve Pack is packed in a Poly Bag with a User Instruction Sheet (UIS)