

Product Data Sheet

Neo Armor™ AS 6-101-B11

Light Weight Work Glove, Nitrile Foam Finish Coated, Machine Knitted Cut Level F, with Thumb Crotch Reinforcement



| | |
|------------------|--|
| Gauge | 13gg |
| Liner | HPPE, Steel, Glass, Nylon, Polyester & Spandex |
| Liner Colours | Black and White |
| Dipping Coverage | Palm Coated |
| Coating | Nitrile foam finish |
| Coating Colour | Black |

Features:

- Unique Nitrile micro-foam finish provides excellent dry, wet and oil grip performance.
- 360 degree breathable coating keeps hand cool and comfortable.
- Ergonomically design for superior fit, feel and comfort.
- Excellent abrasion resistance allows long term use and better durability.
- Complies with REACH directives and uses Azo-free dye.

Applicable Industries:

- Automotive
- Construction
- Manufacturing
- Glass Handling
- General Handling
- Steel & Metal

Glove Type

- General Handling Gloves
- Cut Resistant Gloves
- Abrasion Resistant Gloves

Hazard

- Abrasion
- Cut

95B, Zone A, Export Processing Zone, Biyagama, Malwana, Sri Lanka
+94(0)11 4311 240 | Advansafety.online

Certifications

CE Category ii Certificate

EN 420:2003+A1:2009

EN 388:2016 (4X42F)

EN 388 readings ACTP TDM (F)



Dimensions / Weight

| | | XXS/6 | S/7 | M/8 | L/9 | XL/10 | XXL/11 |
|---|----------------------------------|-------|-------|-------|-------|---------|---------|
| A | Total Glove Length (mm) (±10) | 2 2 0 | 2 3 0 | 2 4 0 | 2 5 0 | 2 6 0 | 2 7 0 |
| B | Wrist Length (mm) (±5) | 7 0 | 7 5 | 7 5 | 8 0 | 8 0 | 8 0 |
| C | Wrist width (mm) (±5) | 7 5 | 7 5 | 8 0 | 8 0 | 8 0 | 8 5 |
| D | Palm width (mm) (±5) | 8 5 | 9 0 | 9 5 | 1 0 0 | 1 0 5 | 1 1 0 |
| | Over lock Color | Blue | Red | Green | White | Yellow | Black |
| | Glove Weight/Pair (g) (±6) | 6 0 | 6 6 | 7 2 | 7 6 | 8 2 | 9 0 |
| | Gross Weight/Pack (g) | 7 7 0 | 8 4 2 | 9 1 4 | 9 6 2 | 1 0 3 4 | 1 1 3 0 |
| | Net Weight/Pack (g) | 7 2 0 | 7 9 2 | 8 6 4 | 9 1 2 | 9 8 4 | 1 0 8 0 |

Packaging

| | |
|-----------------|--|
| Description | Each glove comes with a heat transfer Label Sticker and a Care label. 12 Pairs with a Sleeve Pack is packed in a Poly Bag with a User Instruction Sheet (UIS) |
| Pairs Per Pack | 12 Pairs |
| Pack Dimensions | 260mm x 160mm x 120mm |