

# Product Data Sheet

## Neo Armor™ AS 3-017-B11

Light Weight Work Glove, Nitrile Foam Finish Coated, Machine Knitted Cut Level C/A3, with Thumb Crotch Reinforcement



Gauge	15 gg
Liner	HPPE, Glass, Polyester, Nylon & Spandex
Liner Colours	Melange Blue
Dipping Coverage	Palm Coated
Coating	Nitrile foam finish
Coating Colour	Black

### Features:

- Unique Nitrile micro foam finish provides excellent dry, wet and oil grip performance.
- 360 degree breathable coating keeps hand cool and comfortable.
- Ergonomically design for superior fit, feel and comfort.
- Excellent abrasion resistance allows long term use and better durability.
- Product is Oeko Tex standard certified & treated with sanitized.
- Product is in compliance with reach directives and azo free dyestuff.

### Applicable Industries

- Automotive
- Construction
- Glass Handling
- Mining, Oil & Gas
- Steel & Metal

### Glove Type

- General Handling Gloves
- Cut Resistant Gloves
- Abrasion Resistant Gloves

### Hazard

- Abrasion
- Cut

95B, Zone A, Export Processing Zone, Biyagama, Malwana, Sri Lanka  
+94(0)11 4311 240 | Advansafety.online

### Certifications

CE Category ii Certificate  
EN 420:2003+A1:2009  
EN 388:2016 (4X43C)  
EN 388 readings ACTP TDM (C)  
ASTM F2992-15 (ANSI A3)  
EN 407:2004 (X1XXXX)  
Standard 100 by OEKO-TEX®



### Dimensions / Weight

		XXS/6	S/7	M/8	L/9	XL/10	XXL/11
A	Total Glove Length (mm) (±10)	2 2 0	2 3 0	2 4 0	2 5 0	2 6 0	2 7 0
B	Wrist Length (mm) (±5)	7 0	7 5	7 5	8 0	8 5	8 5
C	Wrist width (mm) (±5)	7 5	7 5	8 0	8 0	8 5	9 0
D	Palm width (mm) (±5)	8 5	9 0	9 5	1 0 0	1 0 5	1 1 0
	Over lock Color	Blue	Red	Green	White	Yellow	Black
	Glove Weight/Pair (g) (±6)	4 6	5 0	5 4	5 8	6 2	6 8
	Gross Weight/Pack (g)	6 0 2	6 5 0	6 9 8	7 4 6	7 9 4	8 6 6
	Net Weight/Pack (g)	5 5 2	6 0 0	6 4 8	6 9 6	7 4 4	8 1 6

### Packaging

Description	Each glove comes with a heat transfer Label Sticker and a Care label. 12 Pairs with a Sleeve Pack is packed in a Poly Bag with a User Instruction Sheet (UIS)
Pairs Per Pack	12 Pairs
Pack Dimensions	260mm x 160mm x 120mm